

STATE OF WASHINGTON
DEPARTMENT OF CONSERVATION
DIVISION OF WATER RESOURCES

Cert # 6103-A

Permit to Appropriate Public Ground Waters
of the State of Washington

Book No. 13 of Ground Water Permits, on page 6078 under Application No. 6352

KENNETH J. CLARKSON

Assign to:

Tonasket, Washington

Plateau Orchard Co.

7-8-68

whereby granted a permit to appropriate the following described public ground waters of the State of Washington, subject to existing rights, and to the limitations and provisions set out herein.

Priority date of this permit is June 21, 1962

Source of the proposed ground water appropriation is a well 3 Wells 1 well *7/10/68*

within _____ area, _____ sub-area _____ zone. Name or number of works is _____

Quantity of water appropriated shall be limited to the amount which can be beneficially applied and not to exceed 2500 gallons per minute; 1000 acre-feet per year, to be used for the following purposes: irrigation

as more definitely set out below.

Location of the well, tunnel, or infiltration trench is approximately 1070 feet south of
300' E of 100' S of NW corner of Sec. 36.
North quarter corner of Sec. 36 - 3, 350' W. of NE. Cor. of NW 1/4 NW 1/4 Sec. 36
NE NW 1/4 & NW 1/4 NE 1/4 1070' E & 25' S from NW corner of Sec. 36

being within NE 1/4 NW 1/4 (Indian Allotment #33) Sec. 36, T. 37 N., R. 26 E.W.M.
Cont. Lot 5, within Ke-mo-dal-kia Indian Allotment No. 33, in
county of Okanogan

Use, or uses to which water is to be applied:

For municipal supply: _____ gallons per minute; _____ acre-feet per year, to supply _____

For irrigation: 2500 gallons per minute; 1000 acre-feet per year, for the irrigation of 250 acres.

For miscellaneous uses: _____ gallons per minute; _____ acre-feet per year, for _____

LEGAL DESCRIPTION OF PROPERTY ON WHICH WATER IS TO BE USED

Lot 11, Sec. 25; Lots 5, 6, 7, 8 and 9, N 1/2 NE 1/4, NE 1/4 NW 1/4, Sec. 36, all in T. 37 N., R. 26 E.W.M.

Lots 6, 7, 8 and 9, Sec. 30; Lots 10, 13, 14 and 15, N 1/2 NW 1/4 in Sec. 31, all in T. 37 N., R. 27 E.W.M.

DESCRIPTION OF WORKS FROM WHICH WATER IS TO BE WITHDRAWN

The well will be drilled and have a diameter of 12 inches, and depth of 100
(Dug or drilled)

Description of tunnel or infiltration trench:

(Please read carefully provisions below)

Particular specifications required by the Supervisor of Water Resources for the purpose of preventing
waste of public waters:

Construction work shall begin on or before December 1, 1963

and shall thereafter be prosecuted with reasonable diligence and completed on or before

December 1, 1964

and complete application of water to proposed use shall be made on or before

December 1, 1965 - 12-1-66 -

12-1-67

Given under my hand and the seal of this office at Olympia, Washington, this 17 day

December, 1962.

M. Walker
State Supervisor of Water Resources